

SAFETY DATA SHEET

HCS-2012 APPENDIX D TO §1910.1200

NO:2026011

Version 1

Product Name warriors ICR14500 500MAH 3.7V Lithium-ion battery

Issue Date 01-Jan-2026

Revision date 01-Jan-2026

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name warriors ICR14500 500MAH 3.7V Lithium-ion battery

Other means of identification

Product Code Voltage: 3.7V
Ampere hour: 100MAH

Recommended use of the chemical and restrictions on use

Recommended Use Power supply
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Suzhou Xinlvzhou Electronics Co., Ltd
Address No. 118 Sanji Road, Xiangcheng District, Suzhou, Jiangsu
Postal Code 215111
Phone +86-512-68702665
FAX +86-512-68669435
E-mail qky006@lvzhoudianzi.com.cn

Emergency telephone number

+86-512-68702665

2. HAZARDS IDENTIFICATION

GHS Classification

Not classified

Label elements

Symbols/Pictograms	None
Signal word	None
Hazard Statements	Not classified
Precautionary Statements	
Prevention	None
Response	None
Storage	None
Disposal	None

Hazards not otherwise classified (HNOC)

Batteries may vent, ignite and produce sparks when subjected to high temperature, when damaged or abused (e.g., mechanical damage); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

This product should not present a health hazard when used under reasonable conditions. If contact with the internal components of the battery may be irritating to skin, eyes and mucous membranes. Fire will produce irritating, corrosive and/or toxic gases. Burning batteries may produce toxic hydrogen fluoride gas. Fumes may cause dizziness or suffocation.

If the battery is discarded into the environment, the harmful contents inside may be dangerous.

Unknown acute toxicity

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature Mixture

Chemical Name	CAS No	Weight-%
Lithium Cobalt Oxide (CoLiO ₂)	12190-79-3	40
Aluminum foil	7429-90-5	29
Carbon black	1333-86-4	21
Copper	7440-50-8	8
Phosphate(1-), hexafluoro-, lithium	21324-40-3	2

4. FIRST AID MEASURES

Description of first aid measures

General advice	No effect under routine handling and use. If exposure to internal materials within cells due to damaged outer metal casing, the following actions are recommended.
Inhalation	If inhaled, remove from exposure and move to fresh air immediately. Rinse mouth and nose with water. Get medical aid immediately. DO NOT use mouth-to-mouth resuscitation. If breathing has ceased apply artificial respiration using oxygen and a suitable mechanical device.
Skin Contact	In case of contact, immediately flush skin with copious amounts of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing and shoes before reuse. Get medical aid.
Eye contact	Rinse immediately with plenty of water during at least 15-30 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easily possible. DO NOT rubbing eyes with hand. Get medical aid immediately.
Ingestion	Do not induce vomiting. If the injured is fully conscious: wash mouth out with water, then give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid immediately.

Most important symptoms and effects, both acute and delayed

See Section 11 for more information.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Toxic vapor may release in case of fire. Thermal shock may cause battery case to crack open. Containers may explode when heated. Firefighting water runoff and dilution water may be toxic and corrosive and may cause adverse environmental impacts. On some bad using conditions (e.g., mechanical damage, external short circuit.) and in case of a bad functioning, some electrolyte can be removed from the cell by the security vent. Exposure to the ingredients contained within the battery pack could be harmful under some circumstances.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate personnel to safe areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Toxic vapor may release in case of fire. Thermal shock may cause battery case to crack open. Containers may explode when heated. Firefighting water runoff and dilution water may be toxic and corrosive and may cause adverse environmental impacts. On some bad using conditions (e.g., mechanical damage, external short circuit.) and in case of a bad functioning, some electrolyte can be removed from the cell by the security vent. Exposure to the ingredients contained within the battery pack could be harmful under some circumstances.

Methods and material for containment and cleaning up

Avoid dispersal of spilled material and runoff and contact with soil, water ways, drains and sewers.

Remove all sources of ignition or heat. Stop leak if safe to do so. Move containers from spill area. Carefully collect undamaged batteries in a clean, dry and appropriate container for reuse or disposal. If electrolyte leaks or spills, collect all released material in an appropriate container before proper disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Conditions for safe storage, including any incompatibilities

Store in a cool and dry area, but prevent condensation on cell or battery terminals. High temperature may damage the performance of the battery. Protect from physical damage and short circuits. To avoid risk of fire or explosion, keep sparks and other sources of ignition away from the battery. Do not allow metal objects to simultaneously contact both positive and negative terminal of batteries. Do not stack battery directly on another battery. Do not store batteries on electrically conductive surfaces.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	Denmark	European Union
Lithium Cobalt Oxide (CoLiO ₂) (CAS #: 12190-79-3)	TWA: 0.02 mg/m ³ Co	-	-	TWA: 0.01 mg/m ³	-
Aluminum foil (CAS #: 7429-90-5)	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 5 mg/m ³ Al	TWA: 5 mg/m ³ TWA: 2 mg/m ³	-
Carbon black (CAS #: 1333-86-4)	TWA: 3 mg/m ³ inhalable fraction	-	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	TWA: 3.5 mg/m ³	-
Copper (CAS #: 7440-50-8)	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	-	IDLH: 100 mg/m ³ dust, fume and mist IDLH: 100 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 1.0 mg/m ³ TWA: 0.1 mg/m ³	-
Phosphate(1-), hexafluoro-, lithium (CAS #: 21324-40-3)	TWA: 2.5 mg/m ³ F	-	-	TWA: 2.5 mg/m ³	-

Chemical Name	Latvia	France	Finland	Germany	Italy
Lithium Cobalt Oxide (CoLiO ₂) (CAS #: 12190-79-3)		-	TWA: 0.02 mg/m ³	Skin	-
Aluminum foil (CAS #: 7429-90-5)	TWA: 2 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 1.5 mg/m ³	TWA: 4 mg/m ³ TWA: 1.5 mg/m ³	-
Carbon black (CAS #: 1333-86-4)		TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	Skin	-
Copper (CAS #: 7440-50-8)	TWA: 0.5 mg/m ³ STEL: 1 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³ STEL: 2 mg/m ³	TWA: 1 mg/m ³ TWA: 0.1 mg/m ³	TWA: 0.01 mg/m ³ Ceiling / Peak: 0.02 mg/m ³ Ceiling / Peak: 0.2 mg/m ³	-
Phosphate(1-), hexafluoro-, lithium (CAS #: 21324-40-3)		-	-	TWA: 1 mg/m ³ Skin	-

Chemical Name	Poland	Portugal	Spain	Switzerland	Netherlands
Aluminum foil (CAS #: 7429-90-5)	TWA: 2.5 mg/m ³ TWA: 1.2 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 3 mg/m ³	-
Copper (CAS #: 7440-50-8)	-	-	-	-	TWA: 0.1 mg/m ³

Chemical Name	Norway	United Kingdom	Australia	Austria	Belgium
Lithium Cobalt Oxide (CoLiO ₂) (CAS #: 12190-79-3)	TWA: 0.02 mg/m ³ STEL: 0.02 mg/m ³	-	-	Skin	-
Aluminum foil (CAS #: 7429-90-5)	TWA: 5 mg/m ³ STEL: 5 mg/m ³	STEL: 30 mg/m ³ STEL: 12 mg/m ³ TWA: 10 mg/m ³ TWA: 4 mg/m ³	10 mg/m ³ 5 mg/m ³	STEL 20 mg/m ³ TWA: 10 mg/m ³	-
Carbon black (CAS #: 1333-86-4)	TWA: 3.5 mg/m ³ STEL: 3.5 mg/m ³	-	3 mg/m ³	-	-
Copper (CAS #: 7440-50-8)	TWA: 0.1 mg/m ³ TWA: 1 mg/m ³ STEL: 0.1 mg/m ³ STEL: 1 mg/m ³	-	1 mg/m ³ 0.2 mg/m ³	STEL 4 mg/m ³ STEL 0.4 mg/m ³ TWA: 1 mg/m ³ TWA: 0.1 mg/m ³	-
Phosphate(1-), hexafluoro-, lithium (CAS #: 21324-40-3)	-	-	2.5 mg/m ³	-	-

Appropriate engineering controls

General room ventilation is sufficient during normal use and handling. Do not install these batteries in sealed, unventilated areas. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Remove jewelry, rings, watches and any other metallic objects while working on battery. All tools should insulate to avoid the possibility of shorting connections. DO NOT lay tools on top of the battery. The work area should be equipped with the corresponding species and quantity of fire equipment and leakage emergency equipment.

Individual protection measures, such as personal protective equipment

Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hand Protection	Under normal condition of use and handling no special protection is required for sealed battery. In the event of battery case breakage, should be wear appropriate safety gloves.
Eye/face protection	Under normal condition of use and handling no special protection is required for sealed battery. Use appropriate safety glasses when there is the risk of splash.
Skin and body protection	Under normal condition of use and handling no special protection is required for sealed battery. It is recommended to wear appropriate protective clothing when the battery case is broken.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Solid
Color	Black
Odor	Odorless
Odor Threshold	Not determined
pH	Not determined
Melting point/freezing point	Not determined
Boiling point / boiling range	Not determined
Flash point	Not determined
Evaporation rate	Not determined
Flammability (solid)	Not flammable
Flammability Limit in Air	Not applicable
Vapor Pressure	Not determined
Vapor density	Not applicable
Density	Not determined
Relative density	Not determined
Bulk density	Not determined
Specific gravity	Not determined
Water solubility	Insoluble in water
Partition coefficient (LogPow)	Not determined
Autoignition temperature	Not applicable
Decomposition temperature	Not determined
Kinematic viscosity	Not determined
Dynamic viscosity	Not determined
Explosive properties	Not an explosive
Oxidizing properties	Not determined

Other information

No information available

10. STABILITY AND REACTIVITY**Reactivity**

Stable under recommended storage and handling conditions (see SECTION 7, handling and storage).

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

When a battery cell is exposed to an external short-circuit, crushed, modification, high temperature, open flames, it will be the cause of heat generation and ignition.

Conditions to avoid

Exposed to an external short-circuit, crushed, modification, high temperature, open flames, incompatible materials, direct sunlight and high humidity.

Incompatible materials

Conductive materials, water, seawater, strong oxidants, strong acid, strong bases, etc.

Hazardous Decomposition Products

In case of a fire or high temperature, metal oxides and irritating/harmful fumes/smoke may be generated.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation	No effect under routine handling and use for sealed battery. If battery is broken, inhale fume and dust may cause upper respiratory irritation and lung irritation.
------------	---

Eye contact	No effect under routine handling and use for sealed battery. Exposure to the electrolyte contained inside the battery may result in irritation.
Skin Contact	No effect under routine handling and use for sealed battery. Exposure to the electrolyte contained inside the battery may result in chemical burns.
Ingestion	No effect under routine handling and use for sealed battery. Harmful if swallowed the electrolyte contained inside the battery. Exposure to the electrolyte contained inside the battery may cause irritation to mouth, esophagus and gastrointestinal system.

Information on toxicological effects**Acute toxicity**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Carbon black (CAS #: 1333-86-4)	> 8000 mg/kg (rat)	> 3000 mg/kg (Rabbit)	-
Copper (CAS #: 7440-50-8)	> 2500 mg/kg bw(rat)	> 2000 mg/kg bw(rat)	=1.03 mg/L/4 h(rat)

Skin corrosion/irritation

No effect under routine handling and use for sealed battery. Exposure to the electrolyte contained inside the battery may result in chemical burns.

Serious eye damage/eye irritation

No effect under routine handling and use for sealed battery. Exposure to the electrolyte contained inside the battery may result in irritation.

Sensitization

No sensitization responses were observed.

Germ cell mutagenicity

No information available

Carcinogenicity

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO ₂) (CAS #: 12190-79-3)	A3	Group 2B	-	-
Carbon black (CAS #: 1333-86-4)	A3	Group 2B	-	-

Reproductive toxicity

No information available

STOT - single exposure

No information available

STOT - repeated exposure

No information available

Aspiration hazard

No information available

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Algae/aquatic plants EC50	Fish LC50	Crustacea EC50
Lithium Cobalt Oxide (CoLiO ₂) (CAS #: 12190-79-3)	-	275 mg/L/96h(Fundulus heteroclitus)	-

Copper (CAS #: 7440-50-8)	0.031 - 0.054 mg/L/96h Pseudokirchneriella subcapitata static 0.0426 - 0.0535 mg/L/72h Pseudokirchneriella subcapitata static	1.25: 96 h Lepomis macrochirus mg/L LC50 static 0.3: 96 h Cyprinus carpio mg/L LC50 semi-static 0.8: 96 h Cyprinus carpio mg/L LC50 static 0.112: 96 h Poecilia reticulata mg/L LC50 flow-through 0.0068 - 0.0156: 96 h Pimephales promelas mg/L LC50 0.3: 96 h Pimephales promelas mg/L LC50 static 0.2: 96 h Pimephales promelas mg/L LC50 flow-through 0.052: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	-
---------------------------	--	--	---

Persistence and degradability
No information available

Bioaccumulative potential
No information available

Mobility in soil
No information available

Other adverse effects
No information available

13. DISPOSAL CONSIDERATIONS

Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations
Contaminated packaging	Dispose of in accordance with federal, state and local regulations

Chemical Name	California Hazardous Waste Status
Lithium Cobalt Oxide (CoLiO2) 12190-79-3	Toxic
Aluminum foil 7429-90-5	Ignitable powder
Copper 7440-50-8	Toxic

14. TRANSPORT INFORMATION

Label for conveyance: Lithium Battery Label, Class 9
UN Number: UN3480 UN3481
Packaging Group: N/A
EmS No: 4.1-06
Marine pollutantNo
Proper Shipping name: Lithium ion batteries
Hazard Classification: The goods shall be complied with the requirements of Section I B of Packing Instructions 965 of 67th DGR Manual of IATA(2024 edition)or special provision188 of IMDG CODE (Amdt42-24)

15. REGULATORY INFORMATION

International Inventories

Component	AICS	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	TSCA
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3 (40%)	X	X	X	X	X	X	-	X
Aluminum foil 7429-90-5 (29%)	X	X	X	Expect	X	X	X	X
Carbon black 1333-86-4 (21%)	X	X	X	X	X	X	X	X
Copper 7440-50-8 (8%)	X	X	X	Expect	X	X	X	X
Phosphate(1-), hexafluoro-, lithium 21324-40-3 (2%)	X	X	X	X	X	X	X	X

"-" Not Listed

"X" Listed

US Federal Regulations

SARA 313

Chemical Name	SARA 313 - Threshold Values %
Aluminum foil - 7429-90-5	1.0

SARA 311/312 Hazard Categories

Not applicable

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8	-	X	X	-

CERCLA

Not applicable

US State Regulations

California Proposition 66

Chemical Name	California Proposition 66
Carbon black - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Lithium Cobalt Oxide (CoLiO ₂) 12190-79-3	X	-	-
Aluminum foil 7429-90-5	X	X	X
Carbon black 1333-86-4	X	X	-
Copper 7440-50-8	X	X	-
Phosphate(1-), hexafluoro-, lithium 21324-40-3	X	-	-

16. OTHER INFORMATION

Revision Note

Issue Date	03-Jan-2026
Revision date	03-Jan-2026
Revision Note	Not applicable

Key or legend to abbreviations and acronyms used in the safety data sheet

- TWA** - TWA (time-weighted average)
STEL - STEL (Short Term Exposure Limit)

Ceiling - Maximum limit value

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

----- **End of Safety Data Sheet** -----