

Material Safety Data Sheet

This report is valid for the current year
Valid until December 31, 2026

Sample name: **Warriors CR1616 3V 50mAh LITHIUM CELL**

Sample model: **CR1616 3V 50mAh**

Applicant: **SUZHOU XINLVZHOU ELECTRONICS CO.,
LTD.**

Date of issue: 2025.12.01

Written by *Chen Jiebi* Approved by *Diana*



Shenzhen Tiansu Calibration and Testing Co., Ltd.



* The MSDS is prepared based on the information provided by client. The contents and formats of this MSDS are revised as per client's request.

Section 1-Chemical Product and Company Identification

Product Name	Warriors CR1616 3V 50mAh LITHIUM CELL
Model	CR1616 3V 50mAh
Series Model	CR3032, CR2477, CR2430, CR2354, CR2050, CR1625, CR1225, CR1130, CR1025, CR927
Trade Mark	WARRIORS
Ratings	3V/50mAh
Weight	1.11g
Lithium content	0.0145g
Manufacturer	SUZHOU XINLVZHOU ELECTRONICS CO., LTD.
Manufacturer Address	SHANJI ROAD 158,XIANGCHENG DISTRICT,SUZHOU CITY,JIANGSU,CHINA.
Emergency Telephone	13285108519
Fax	-

Section 2- Hazards Identification

Emergency overview	N/A
Label elements:	
Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable
Hazard statement(s)	Not Applicable
Precautionary statement(s):	
Prevention	Not Applicable
Response	Not Applicable
Disposal	Not Applicable



Environmental hazards:	No relevant information
Important symptoms:	See section 11 for more information

Section 3– Composition Information

Chemical Composition	CAS No.	Weight (%)
Stainless Steel	12597-68-1	45 to 60
Manganese Dioxide	1313-13-9	15 to 40
Propylene Carbonate	108-32-7	2 to 6
1,2-Dimethoxyethane	110-71-4	1 to 5
1,3-Dioxolane	646-06-0	1 to 5
Lithium Perchlorate	7791-03-9	0 to 1.5
Lithium or Lithium Alloy	7439-93-2	1 to 5
Graphite	7782-42-5	1 to 4
Polypropylene	9003-07-0	3 to 10
Glass Fiber	65997-17-3	1 to 2
Pb	7439-92-1	<0.0040
Hg	7439-97-6	<0.0005
Cd	7440-43-9	<0.0020

Section 4– First Aid Measures

Eye contact	Flush eyes with plenty of water for least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin contact	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

Section 5– Fire Fighting Measures

Flash Point	N/A
--------------------	-----



Auto-Ignition Temperature	N/A
Extinguishing Media	Hydrocarbon surfactant, CO ₂
Special Fire-Fighting Procedures	Self-contained breathing apparatus
Unusual Fire and Explosion Hazards	Cell may vent when subjected to excessive heat-exposing battery contents
Hazardous Combustion Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 6– Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate, Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed by using sand, earth or other inert substance and contaminated area should be ventilated meantime.

Environment precautions:

Do not allow product to reach sewage system or any water source.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules, Avoid leached substances to get into the earth, canalization or waters.

Section 7– Handling and Storage

Handling	The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.
Storage	Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.



Other Precautions	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.
--------------------------	--

Section 8– Exposure Controls/Personal Protection

Engineering Controls	Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.
Personal Protective Equipment	Respiratory Protection: Not necessary under normal conditions. Skin and body Protection: Not necessary under normal conditions, Wear suitable protective clothing and gloves if handling an open or leaking battery. Hand protection: Wear suitable gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.

Section 9– Physical and Chemical Properties

Color	Silver
Odour	Not Applicable
pH	Not Applicable
Melting point/freezing point	Not Applicable
Boiling Point and Boiling range	Not Applicable
Flash Point	Not Applicable
Upper/lower flammability or explosive limits	Not Applicable
Vapor Pressure	Not Applicable
Vapor Density	Not Applicable



Relative density	Not Applicable
Solubility in Water	Not Applicable
Auto-ignition temperature	Not Applicable
Decomposition temperature	Not Applicable
Evaporation rate	Not Applicable
Flammability (soil, gas)	Not Applicable
Viscosity	Not Applicable

Section 10- Stability and reactivity

Stability	The product is stable under conditions described Section 7
Conditions to Avoid	Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions.
Incompatible Materials	Oxidizing agents, acid, base.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.
Possibility of Hazardous Reaction	Not Applicable

Section 11 - Toxicological Information

Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.
Sensitization	Not Applicable
Neurological Effects	Not Applicable
Teratogenicity	Not Applicable
Reproductive Toxicity	Not Applicable
Mutagenicity (Genetic Effects)	Not Applicable
Toxicologically Synergistic Materials	Not Applicable



Section 12- Ecological Information

Ecological Toxicity	Not Applicable
Mobility in soil	Not Applicable
Persistence and Degradability	Not Applicable
Bioaccumulation potential	Not Applicable
Other Adverse Effects	Not Applicable

Section 13- Disposal Considerations

Product disposal recommendation	Observe local, state and federal laws and regulations.
Packaging disposal recommendation	Disposal must be made according to official regulations

Section 14 - Transport Information

UN Number	UN 3090 or UN 3091	
Packing group	---	
Marine pollutant	No	
UN Proper shipping name	Lithium Metal Batteries (including lithium alloy batteries) Lithium Metal Batteries Contained In Equipment (including lithium alloy batteries) Lithium Metal Batteries Packed With Equipment (including lithium alloy batteries)	
ICAO/IATA	Transport hazard class(es)	Class 9 (968IB) or N/A (969~970 II)
	Can be shipped by air in accordance with international Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA) DGR 67 th Packing Instructions Section IB of 968 or Section II of 969~970 appropriately.	
IMDG CODE	International Maritime Dangerous Goods Code under Special Provision 188 IMDG CODE (Amdt 42-24)	



ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road under Special Provision 188
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail under Special Provision 188

The dangerous goods regulations require that each battery design be subject to tests contained in Section 38.3 of the UN Manual of Tests and Criteria prior to being offered for transport.

Section 15– Regulatory information

Law information

《Dangerous Goods Regulations》
 《Recommendation on the Transport of Dangerous Goods Model Regulations》
 《International Maritime Dangerous Goods》
 《Technical Instructions for the Safe Transport of Dangerous Goods》
 《Classification and code of dangerous Goods》
 《Consumer Product Safety Act》 (CPSA)
 《Federal Environmental Pollution Control Act》 (FEPCA)
 《Resource Conservation and Recovery Act》 (RCRA)
 《European Agreement concerning the International Carriage of Dangerous》
 《Regulations concerning the International Carriage of Dangerous》

In according with all Federal, State and local laws.

Section 16– Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, this document makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

— End of Report —

